

VEE RAY SINGLE PAN GAS FRYER 450mm

GT45E

- High performance single pan fryer
- Patented infra-red burner system
- Digital display temperature control with 3 product timers
- Easy clean stainless steel open pan with 10 year limited warranty
- 20L oil capacity
- Large capacity cool zone
- 32mm (1 ¹/₄") drain valve
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



GT45F

Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- \bullet 32mm (1 $^{1}/_{4}$ ") drain valve
- 63mmdia. heavy-duty 1.2mm304stainless steeladjustable legs at front and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

Control

- Digital display electronic thermostat
- Thermostat range 88-193°C
- \bullet 3 programmable product timers with countdown display and alarms
- Straight or temperature compensating cook time control
- Heating and basket drop displays
- Programmable melt cycles
- Over-temperature safety cut-out
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pan for easy clean
- Easy clean basket support bar
- 32mm (1 $^{1}/_{4}$ ") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit





VEE RAY SINGLE PAN GAS FRYER 450mm

GT45E

Specifications

Production rate

31kg/hr

Pan size

Oil capacity 20L (37lbs shortening) Width 365mm Length 380mm Oil frying depth 95mm

Baskets

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

2 x 45MJ/hr infra-red burners

Gas power

90MJ/hr, 25kW

Gas connection

R 3/4 (BSP) male Optional rear connection (refer specification drawing)

Electrical connection

230-240 Vac, 1P+N+E, 50/60Hz, 0.5A 3 pin 10A plug cordset fitted

Dimensions

Width 450mm Depth 812mm

Height 915mm

Incl. splashback 1085mm

Nett weight

81kg

Packing data

0.54m3, 122kg

Width 870mm

Depth 495mm

Height 1255mm

Gas types


Available in Natural gas and LP gas, please specify when ordering Units supplied complete with gas type

conversion kits

Other gas types on request

Options

Adjustable feet at rear Filtamax Filtration System Fish plates Extra baskets Side splash guards Joining caps Castors





MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





IS09001 Quality Management SGS Standard



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.01.19/1620