

#### Modular Cooking Range Line 900XP Electric Bain Marie Top Full module



#### Modular Cooking Range Line

## 900XP Electric Bain Marie Top Full module

391125 (E9BMEHB000)

900XP ELECTRIC BAIN MARIE TOP, FULL MODULE -400 V

#### **Short Form Specification**

#### Item No.

Incoloy armoured heating elements positioned under the base of the well. Used to keep cooked food at serving temperature using hot water inside the well. Water temperature to be controlled by thermostat with maximum temperature of 90 °C. Exterior panels of unit in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

ITEM #		
MODEL #		
NAME #		
<u>SIS #</u>		
AIA #		

#### Main Features

- Bain Marie used for keeping cooked food at serving temperatures using hot water.
- Incoloy armoured heating elements positioned under the base of the well.
- Knob switch.
- Water basin is seamlessly welded into the top of the appliance.
- Filling water level is plate-marked on the side of the well.
- Unit to feature manual refill of well.
- Water temperature controlled by thermostat with maximum temperature value of 90 °C.
- Basin drained by drain valve with overflow.
- Special insulation beneath cooking surface keeps heat on the plate without dispersion to the base.
- Unit to have perforated false bottom and runner support for GN containers.
- All major compartments located in front of unit for ease of maintenance.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.

#### Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.


#### **Optional Accessories**

<ul> <li>Junction sealing kit</li> </ul>	PNC 206086
Water column extension for 900 line	PNC 206290
• Side handrail-right/left hand (900XP)	PNC 216044
<ul> <li>Frontal handrail, 800mm</li> </ul>	PNC 216047
<ul> <li>Large handrail - portioning shelf, 800mm</li> </ul>	PNC 216186

Electrolux

APPROVAL:

# Electrolux



### Modular Cooking Range Line 900XP Electric Bain Marie Top Full module

#### Electric

Supply voltage: 391125(E9BMEHB000) Total Watts:	400 V/2N ph/50/60 Hz 4.4 kW
Water:	
Water Drain:	50 mm
Key Information:	
Usable well dimensions (width):	630 mm
Usable well dimensions (height):	160 mm
Usable well dimensions (depth):	685 mm
Thermostat Range:	30 °C MIN; 90 °C MAX
Net weight:	45 kg
Shipping weight:	65 kg
Shipping height:	540 mm
Shipping width:	980 mm
Shipping depth:	1020 mm
Shipping volume:	0.54 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

> Modular Cooking Range Line 900XP Electric Bain Marie Top Full module

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.